



Conmix ConTape

Self Adhesive Viscoelastic Waterproofing Tape

DESCRIPTION

Conmix ConTape is a high performance self adhesive cold applied tape composed of a layer of viscoelastic butyl and a non-woven geotextile backing. The backing material strengthens the tape in transversal longitudinal direction.

USES

Conmix ConTape is used to provide waterproof flexible bridge over all joints, intersections, cracks, cuts, gaps, overlaps, etc. on concrete, wood, metal and variety of substrates. It is used in wet areas, bathrooms, kitchens, pods, etc. It is an excellent means to waterproof overlapping joints on profiled metal roofs, J-hooks, metal gutters, etc. It is used to provide waterproof transition media for various liquid applied waterproofing membranes at corners, covings, sharp edges, peripheral areas of pipe outlets, etc.

ADVANTAGES

- Excellent waterproofing characteristics
- Strong adhesion to all substrates
- Suitable surface to receive plaster and various waterproofing compounds
- Good elongation
- High durability
- Low cost of maintenance
- Self adhesive
- Wide service temperature range

TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Component	-	Single
Form	-	Self adhesive mastic tape
Colour	-	Grey
Application Temperature	-	+5°C to +40°C
Service Temperature	-	-30°C to +80°C

SURFACE PREPERATION

Surfaces must be clean, dry, free of dust, loose particles, etc. Cracks should be routed and repaired with **ReCon GP** or **ReCon FCE**. Surface to be treated with **Conmix ConTape** should be smoothened by grinding or by application of fairing coat material to improve the bond.

APPLICATION

Remove the release paper from **Conmix ConTape**. Press down firmly to avoid air bubbles. To avoid any possible de-bonding, take care that the tape follows the profile of substrate.

PACK SIZE

80 mm width, 10 running mtr rolls. Other sizes available on request.



Conmix ConTape

NOTE

Conmix ConTape is sensitive to solvents. Before application of any solvent based coatings, consult **Conmix Ltd.**

GENERAL INFORMATION

Shelf Life	3 years from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature / humidity may reduce shelf life.
Cleaning	Clean all equipments and tools with Conmix Cleaner immediately after use.

HEALTH and SAFETY

PPE's	Gloves, goggles and suitable mask must be worn.
Precautions	Contact with skin, eyes, etc. must be avoided.
Hazard	Regarded as hazardous for transportation
Disposal	Do not reuse containers. To be disposed off as per local rules and regulations.
Additional Information	Refer MSDS. (Available on request.)

TECHNICAL SERVICE

CONMIX Technical Services are available on request for onsite support to assist in the correct use of its products.

Manufacturer:

CONMIX LTD.

P.O. Box 5936, Sharjah
United Arab Emirates
Tel: +971 6 5314155
Fax: +971 6 5314332
Email: conmix@conmix.com

Sales Office:
Tel: +971 6 5682422
Fax: +971 6 5681442
www.conmix.com



It is the customer's responsibility to satisfy themselves by checking with the company whether information is still current at the time of use. The customer must be satisfied that the product is suitable for the use intended. All products comply with the properties shown on current data sheets. However, Conmix does not warrant or guarantee the installation of the products as it does not have any control over installation or end use of the product. All information and particularly the recommendations relating to application and end use are given in good faith. The products are guaranteed against any manufacturing defects and are sold subject to Conmix standard terms and conditions of sale.