



SealXtra Primer

Primer for Joint Sealants

DESCRIPTION **SealXtra Primer** is based on silane modified polyether which forms a durable primer for sealant.

USES **SealXtra Primer** is used as a primer for cold applied elastomeric sealants. It can be used on a variety of surfaces like concrete, steel, glass, aluminum, etc.

ADVANTAGES

- Can be used for variety of elastomeric sealants
- Suitable for variety of substrates
- Highly penetrating
- Seals joint surface, restricts air rising from the substrate
- Reduces bubble formation in sealant

TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Component	-	Single
Form	-	Liquid
Colour	-	Clear
Specific Gravity	ASTM D1475	0.89 +/- 0.02
Drying time	-	5-15 mins

SURFACE PREPARATION Joint surfaces must be clean, dry and free of dust, grease, curing compound, etc. New concrete surfaces must be dry and at least 3 weeks old. In case of old joints, traces of previous sealant and other contaminants should be removed by mechanical means to ensure a clean surface.

APPLICATION Stir well before use. Joint surfaces should be primed with **SealXtra Primer** before application of sealant. Brush apply primer to vertical surfaces of joint. Excessive application and puddling of primer should be avoided.

PACK SIZE 1 ltr

CONSUMPTION 1% to 3% of volume of joint sealant. Actual consumption depends on porosity of substrate.

LIMITATIONS For use with natural stone, possibility of staining should be checked prior to use.

GENERAL INFORMATION

Shelf Life 12 months from date of manufacture, if stored properly in original unopened packing under warehouse conditions. Extreme temperature / humidity may reduce shelf life.

Cleaning Clean all equipments and tools with **Conmix Cleaner**.



SealXtra Primer

HEALTH and SAFETY

PPE's

Gloves, goggles and suitable mask must be worn.

Precautions

Contact with skin, eyes, etc. must be avoided. If swallowed, seek medical attention immediately.

Hazard

Regarded as hazardous for transportation.

Disposal

Do not reuse containers. To be disposed off as per local rules and regulations.

Additional Information

Refer MSDS. (Available on request.)

TECHNICAL SERVICE

CONMIX Technical Services are available on request for onsite support to assist in the correct use of its products.

Manufacturer:

CONMIX LTD.

P.O. Box 5936, Sharjah
United Arab Emirates
Tel: +971 6 5314155
Fax: +971 6 5314332
Email: conmix@conmix.com

Sales Office:

Tel: +971 6 5682422
Fax: +971 6 5681442
www.conmix.com



It is the customer's responsibility to satisfy themselves by checking with the company whether information is still current at the time of use. The customer must be satisfied that the product is suitable for the use intended. All products comply with the properties shown on current data sheets. However, Conmix does not warrant or guarantee the installation of the products as it does not have any control over installation or end use of the product. All information and particularly the recommendations relating to application and end use are given in good faith. The products are guaranteed against any manufacturing defects and are sold subject to Conmix standard terms and conditions of sale.