



# ReForm T

Special Emulsion Based Form Release Agent  
for Severe Weather Conditions

**DESCRIPTION** A premium mould oil specifically developed for harsh climatic conditions where high performance is required. **ReForm T** gives excellent resistance to rain and performs well where steel moulds have high surface temperatures. A ready to use liquid which outperforms standard mould oils.

**USES** **ReForm T** is designed to be used with all types of moulds (metal, rubber, wooden) providing fast easy release and clean fair face concrete. Used on forms for precast concrete, in-situ concrete, high performance sticky concrete, self compacted concrete, slip form concrete, stamped concrete, etc.

**ADVANTAGES**

- Reduces surface pinholes
- Does not wash away in rain
- Performs well in extreme ambient temperatures and humidity levels
- Ready to use
- Produces clean fair face finish
- Does not stain concrete surface
- Non toxic
- Does not rust moulds

## TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Component	-	Single
Form	-	Liquid
Colour	-	Milky White
Specific Gravity	ASTM D1475	0.99 +/- 0.05

**SURFACE PREPARATION** Moulds must be dry, clean, free of rust and foreign matter prior to the application of **ReForm T**. Any surface repairs done with putty should be totally cured and dry. Moulds should be protected from dust storm or rain during application.

**APPLICATION** **ReForm T** is ready to use and should be applied as thin and evenly as possible. Stir well before use. Apply by spray, roller or sponge, excess material should be removed by sponge before pouring concrete.

**PACK SIZE** 5 ltr, 20 ltr and 200 ltr

**COVERAGE** 20-30 m<sup>2</sup>/ltr/coat (coverage depends on surface finish, porosity and texture)



## ReForm T

<b>GENERAL INFORMATION</b>	<b>Shelf Life</b>	12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature / humidity may reduce shelf life.
	<b>Cleaning</b>	Clean all equipments and tools with <b>Conmix Cleaner</b> immediately after use.
<b>HEALTH and SAFETY</b>	<b>PPE's</b>	Gloves, goggles and suitable mask must be worn.
	<b>Precautions</b>	Contact with skin, eyes, etc. must be avoided. If swallowed seek medical attention immediately.
	<b>Hazard</b>	Regarded as non-hazardous for transportation.
	<b>Disposal</b>	Do not reuse containers. To be disposed off as per local rules and regulations.
	<b>Additional Information</b>	Refer MSDS. (Available on request.)
<b>TECHNICAL SERVICE</b>	<b>CONMIX Technical Services</b> are available on request for onsite support to assist in the correct use of its products.	

**Manufacturer:**

**CONMIX LTD.**

P.O. Box 5936, Sharjah  
United Arab Emirates  
Tel: +971 6 5314155  
Fax: +971 6 5314332  
Email: conmix@conmix.com

Sales Office:  
Tel: +971 6 5682422  
Fax: +971 6 5681442  
[www.conmix.com](http://www.conmix.com)



It is the customer's responsibility to satisfy themselves by checking with the company whether information is still current at the time of use. The customer must be satisfied that the product is suitable for the use intended. All products comply with the properties shown on current data sheets. However, Conmix does not warrant or guarantee the installation of the products as it does not have any control over installation or end use of the product. All information and particularly the recommendations relating to application and end use are given in good faith. The products are guaranteed against any manufacturing defects and are sold subject to Conmix standard terms and conditions of sale.