

JetCure WB

Water Based Concrete Curing Compound

DESCRIPTION	1
-------------	---

JetCure WB is a ready to use water based wax emulsion curing compound, used to prevent moisture evaporation from the concrete surface. It forms a continuous film providing a barrier to premature moisture loss ensuring effective hydration of cement.

STANDARDS

ASTM C309 Type 1, Type 2, Class A and BS 8110-1

USES

JetCure WB is used as curing compound for exposed concrete surfaces like roads, runways, aprons, precast concrete, decks, hardstands, underground concrete surfaces, columns, beams, etc.

ADVANTAGES

- · Protects concrete surfaces against premature loss of moisture
- · Solvent free, environment friendly
- · Easy application
- · Reduces plastic shrinkage cracks
- Economical
- · Labour saving
- · Provides better hydration of cement

TYPICAL PROPERTIES at 25°C

PROPERTY	TEST METHOD	VALUE
Component	-	Single
Form	-	Liquid
Colour	-	White
Specific Gravity	ASTM D1475	1.00 +/- 0.05
Curing Efficiency	BS 7542	> 90%
	ASTM C156	< 0.55kg/m²

SURFACE PREPARATION

Concrete surface should be free from mould release agents, standing or bleed water and other impurities.

APPLICATION

JetCure WB being a water based wax emulsion should be stirred thoroughly by rolling the drum before use to ensure even dispersion. It is ready to use and should not be diluted.

JetCure WB is generally recommended for use on concrete where subsequent coatings, mortar or renders will not be applied. It should be applied as soon as the formwork of vertical sections is removed. In case of horizontal surfaces, it should be applied once the free surface water or bleed water has disappeared. **JetCure WB** being in white liquid form, provides a visual guide during application. It dries to form a continuous clear film. **JetCure WB** can be applied by using knapsack spray, roller, brush, etc.

CC/JC08/Ver5/01/11 1/2 Technical Datasheet

Construction Chemicals



JetCure WB

NOTE	JetCure WB wax film degrades under environmental action. Time duration of degradation depends on intensity of exposure. JetCure WB film should be removed prior to application of screeds or coatings.		
PACK SIZE	5 ltr, 20 ltr and 200 ltr		
COVERAGE	5-6 m²/ltr/coat (depending on surface finish, porosity and texture)		
GENERAL INFORMATION	Shelf Life Cleaning	12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature / humidity may reduce shelf life. Clean all equipments and tools with Conmix Cleaner immediately after use.	
HEALTH and SAFETY	PPE's Precautions	Gloves, goggles and suitable mask must be worn. Contact with skin, eyes, etc. must be avoided. If swallowed seek medical attention immediately.	
	Hazard	Regarded as non-hazardous for transportation.	
	Disposal	Do not reuse containers. To be disposed off as per local rules and regulations.	
	Additional Information	Refer MSDS. (Available on request.)	
TECHNICAL SERVICE	CONMIX Technical Services are available on request for onsite support to assist in the correct use of its products.		

Manufacturer:
CONMIX LTD.
P.O. Box 5936, Sharjah
United Arab Emirates
Tel: +9971 6 5314155
Fax: +971 6 5314332
Email: conmix@conmix.com

Sales Office: Tel: +971 6 5682422 Fax: +971 6 5681442 www.conmix.com



It is the customer's responsibility to satisfy themselves by checking with the company whether information is still current at the time of use. The customer must be satisfied that the product is suitable for the use intended. All products comply with the properties shown on current data sheets. However, Conmix does not warrant or guarantee the installation of the products as it does not have any control over installation or end use of the product. All information and particularly the recommendations relating to application and end use are given in good faith. The products are guaranteed against any manufacturing defects and are sold subject to Conmix standard terms and conditions of sale.